Introducing SES 3.0

BOOTH 3041

Stoner Engineering LLC Golden, Colorado

www.makinhole.com

SES 3.0

Dr. Michael S. Stoner – Founder
SES = Stoner Engineering Software

- Directional/Horizontal planning & execution software
- Steering is main focus
- SES 3.0 significant enhancements
 - Realistic Wellsite 3D Geosteering
 - Realistic Wellsite Steering Guidance (Patented Fuzzy Logic Controller)





Planning & Surveying



3D planner and survey calc FREE since 2000 at www.makinhole.com



STONER ENGINEERING LLC

Planning & Surveying



• 3D survey data viewer (rotate/zoom/pan)





STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



Geologic Model



Model

STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



Geologic Model



STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



Location of payzone relative to well



US Directional & Horizontal Rigs

 Challenge on every horizontal well

Source: http://www.bakerhughes .com/investor/rig/rig_na. htm

STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



Ourrent Practice

- 2D with Vertical Section View
- Dependent on service companies for directional calculations

• Go 3D

- Why?
- What is meant by "3D"? How?
- New geologic terminology





Why go 3D?

A. Eliminate distortion from V.S. projection

What is meant by "3D"? How?
New geologic terminology





Why go 3D?
A. Eliminate distortion from V.S. projection
What is meant by "3D"? How?

- 3DStratBlock
- RSD





New geologic terminology

San Antonio SPE ATCE 2006

• Why go 3D? - A. Eliminate distortion from V.S. projection • What is meant by "3D"? How? A. 3DStratBlocks & RSD New geologic terminology 3DStratBlock...planar surface that defines the geologic payzone marker bed top (or base) over a finite MD range of the associated survey - Relative Stratigraphic Depth (RSD)...minimum distance to the 3DStratBlock from the wellbore location that emitted the LWD signal





San Antonio SPE ATCE 2006



San Antonio SPE ATCE 2006



San Antonio SPE ATCE 2006



THD...since 2000

Technical Hole Deviation (THD)

- quantifies how a dir. well path differs from its planned trajectory
- any type of dir. drilling
- any type of dir. drilling system
- any planned well path profile
- Log/Table formats
- Geometry OR Geosteer
- No distortion like vertical section projection



THD Components



THD Component	Description	Deviation "Sense"	Unit	Order	Lineal Deviation	Angular Deviation	Verbal Descriptor	
msVD	vertical deviation	Vertical	ft or m	1st	Х		High/Low	
RCVD	relative change in vertical deviation	Vertical	ft/1000ft or m/304.8m	2nd	х		Positive/Negative	
msID	inclinational deviation	Vertical	deg	1st		х	High/Low	
RCID	relative change in inclinational deviation	Vertical	deg/100ft or deg/30.48m	2nd		х	Positive/Negative	
msHD	horizontal deviation	Horizontal	ft or m	1st	х		Left/Right	
RCHD	relative change in horizontal deviation	Horizontal	ft/1000ft or m/304.8m	2nd	x		Positive/Negative	
ms AD	azimuthal deviation	Horizontal	deg	1st		х	High/Low	
RCAD	relative change in azimuthal deviation	Horizontal	deg/100ft or deg/30.48m	2nd		x	Positive/Negative	

STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



San Antonio SPE ATCE 2006



San Antonio SPE ATCE 2006



THD....Why?

Monitor progress; convey details
Rationalization of tool settings / mode
System input for steering automation
Guidance to directional driller

How to systematize a rule-based process?
What technology?













What do these commercial products have in common...









































Fuzzy Logic for Steering



STONER ENGINEERING LLC

San Antonio SPE ATCE 2006



Steering Guidance

	MD	∆ High/Low Side	A Right/Left Side	- VD	RCVD	ID	RCID -	HD	RCHD	AD	RCAD -
	5888.00			-		1.14	0.1				-
	5920.00			-		0.97	-0.5				
	5950.00			- 1.33		-0.23	-4.0				
	5981.00	Towards BUILD 80%		- 0.88	-14	-1.36	-3.6				
	6011.00	Towards BUILD 100%		0.18	-35	-2.67	-4,4				-
	6043.00	Towards BUILD 100%		2.12	-61	-4.21	-4.8				-
	6074.00	Towards BUILD 100%		4.91	-91	-6.02	-5.9				
	6105.00	Towards BUILD 100%		8.56	-120	-7.46	-4.7	-55.54		6.12	
	6135.00	Towards BUILD 100%	Towards LEFT 30%	12.62	-139	-8.02	-1.9	-55.18	12	8.14	6.9 -
	6165.00	Towards BUILD 90%	Towards RIGHT 20%	16.80	-143	-7.86	0.5	-54.68	17	6.91	-4.2 -
	6198.00	Towards BUILD 90%	Towards LEFT 30%	21.32	-142	-7.74	0.4	-54.01	21	6.93	0.1 -
	6229.00	Towards BUILD 100%	NO CHANGE	25.55	-142	-7.81	-0.2	-53.28	24	6.05	-3.0 -
	6259.00	Towards BUILD 100%	Towards LEFT 40%	29.72	-145	-7.96	-0.5	-52.39	31	7.87	6.3 -
	6291.00	Towards BUILD 100%	Towards LEFT 40%	34.52	-158	-8,86	-3.0	-50.90	49	11.83	13.0 -
	6323.00	Towards BUILD 100%	Towards LEFT 50%	39.95	-180	-9.83	-3.2	-48.76	71	14.55	9.1 -
	6354.00	Towards BUILD 80%	Towards LEFT 20%	45.41	-189	-9.48	1.2	-46.33	84	13.67	-3.1 -
	6384.00	Towards BUILD 80%	NO CHANGE	50.47	-182	-9.05	1.5	-43.92	87	12.00	-6.0 -
	6416.00	Towards BUILD 80%	Towards LEFT 50%	55.61	-174	-8.56	1.6	-41.24	91	11.92	-0.3 -
	6447.00	Towards BUILD 80%	Towards LEFT 60%	60.20	-162	-7.56	3.5	-38,36	101	11.92	0.0 -
	6479.00	Towards BUILD 80%	Towards LEFT 30%	64.43	-145	-6.71	2.9	-35.19	109	11.21	-2.4 -
	6511.00	Towards BUILD 80%	Towards LEFT 50%	68.25	-131	-6.02	2.3	-31.77	117	11.65	1.5 -
	6542.00	Towards BUILD 90%	Towards LEFT 60%	71.78	-126	-5.97	0.2	-28.07	132	12.27	2.2 -
	6573.00	Towards BUILD 100%	Towards LEFT 40%	75.35	-128	-6.16	-0.7	-24.15	140	11.97	-1.1 -
	6603.00	Towards BUILD 80%	NO CHANGE	78.41	-113	-4.53	6.0	-20.42	138	10.49	-5.5 -
	6634.00	Towards BUILD 80%	NO CHANGE	80.58	-78	-2.79	6.2	-16.97	124	8.23	-8.1 -
	6665.00	Towards BUILD 80%	NO CHANGE	82.07	-53	-2.28	1.8	-14.18	100	6.03	-7.9 -
	6697.00	Towards BUILD 50%	Towards LEFT 10%	82.77	-24	0.01	7.9	-11.82	82	5.01	-3.5 -
	6727.00	Towards DROP 60%	Towards LEFT 30%	82.16	23	2.52	9.3	-9.78	76	4.60	-1.5 -
	6759.00	Towards DROP 60%	Towards LEFT 60%	80.56	55	3.39	3.0	-7.59	76	4.62	0.1 -
	6771.00	Towards DROP 60%	Towards LEFT 60%	79.76	74	4.45	9.8	-6.73	80	4.84	2.0 -
	6855.00	Towards DROP 60%	Towards RIGHT 20%	69.73	132	9.37	6.5	-2.46	56	1.63	-4.2 -
	6887.00	Towards DROP 60%	Towards RIGHT 20%	64.41	183	9.79	1.5	-1.85	21	0.67	-3.3 -
	6918.00	Towards DROP 40%	Towards RIGHT 40%	59.15	186	9.74	-0.2	-1.80	2	-0.48	-4.1 -
	6950.00	Towards DROP 60%	Towards RIGHT 20%	53.63	188	10.14	1.4	-2.08	-10	-0.56	-0.3 -
	6980.00	Towards DROP 60%	Towards RIGHT 20%	- 47.83	210	12.16	7.3	-2.40	-11	-0.65	-0.3 -
	7011.00	Towards DROP 60%	Towards RIGHT 60%	40,88	241	13.83	5.8	-3.01	-21	-1.62	-3.4 -
	7042.00	NO CHANGE	Towards RIGHT 10%	33.80	244	12.58	-4.3	-3.74	-25	-1.09	1.8 -
	7073.00	NO CHANGE	Towards RIGHT 60%	27.25	223	11.85	-2.5	-4.50	-26	-1.71	-2.1 -
	7104.00	NO CHANGE	Towards RIGHT 10%	21.32	200	10.22	-5.5	-5.25	-25	-1.09	2.1 -
۲	7135.00	NO CHANGE	Towards RIGHT 60%	15.95	179	9.71	-1.7	-6.01	-25	-1.71	-2.1 -
Ren	ord: 🗔 l -		• [].* of 96		•						

STONER ENGINEERING LLC



Steering Guidance

	MD	A High/Low Side	A Right/Left Side	٧D	REVD	ID	RCID -	HD	RCHD	AD	RCAD -
	9004.00	Towards DROP 20%	Towards LEFT 50%	2.07	17	0.65	-0.7	12.90	15	0.23	-1.3 -
	9098.00	Towards DROP 100%	Towards LEFT 60%	4.36	24	2.08	1.5 -	13.71	9	0.75	0.6 -
	9190.00	Towards BUILD 60%	Towards LEFT 60%	1.42	-32	-0.39	-2.7	14.85	12	0.67	-0.1 -
	9222.00	Towards DROP 10%	Towards LEFT 60%	1.22	-6	-0.30	0.3 -	15.22	12	0.67	0.0 -
	9285.00	Towards BUILD 20%	Towards LEFT 70%	0.84	-6	-0.39	-0.1	16.24	16	1.19	0.8 -
	9316.00	Towards BUILD 40%	Towards LEFT 50%	0.60	-8	-0.48	-0.3 -	16.70	15	0.49	-2.3 -
	9380.00	Towards DROP 90%	Towards LEFT 60%	3.10	39	0.23	1.1 -	17.49	12	0.93	0.7 -
	9473.00	Towards DROP 50%	Towards LEFT 80%	3.35	3	0.06	-0.2	19.50	22	1.55	0.7 -
	9566.00	Towards DROP 90%	Towards LEFT 80%	3.39	0	2.83	3.0 -	22.87	36	2.60	1.1 -
	9660.00	Towards DROP 80%	Towards LEFT 80%	6,93	38	1.25	-1.7 -	27.34	48	2.86	0.3 -
	9691.00	Towards DROP 100%	Towards LEFT 70%	7.69	25	1.34	0.3 -	28.82	48	2.60	-0.8 -
	9754.00	Towards BUILD 20%	Towards LEFT 80%	2.57	-81	-0.40	-2.8	31.67	45	2.60	0.0 -
	9849.00	Towards BUILD 50%	Towards LEFT 60%	1.43	-12	-1.02	-0.7 -	35.25	38	1.72	-0.9 -
	9880.00	Towards BUILD 70%	Towards LEFT 70%	0.84	-19	-1.19	-0.5 -	36.25	32	1.98	0.8 -
	9942.00	Towards DROP 30%	Towards LEFT 50%	0.32	-8	0.21	2.3 -	37.64	22	0.58	-2.3 -
	10035.00	Towards DROP 50%	Towards LEFT 50%	0.92	7	0.52	0.3 -	38.43	9	0.40	-0.2 -
	10128.00	Towards DROP 80%	Towards LEFT 70%	2.08	12	0.88	0.4 -	39.80	15	1.28	0.9 -
	10223.00	Towards BUILD 10%	Towards LEFT 70%	1.37	-7	0.15	-0.8	41.84	22	1.19	-0.1 -
	10315.00	Towards DROP 20%	Towards LEFT 60%	1.51	2	-0.02	-0.2 -	43.47	18	0.84	-0.4 -
	10409.00	NO CHANGE	Towards LEFT 50%	1.50	0	-0.44	-0.4 -	43.91	5	-0.30	-1.2 -
	10501.00	Towards DROP 80%	Towards LEFT 40%	2.07	6	0.80	1.3 -	43.15	-8	-0.65	-0.4 -
	10595.00	Towards DROP 40%	Towards LEFT 50%	2,42	4	-0.26	-1.1 -	42.37	-8	-0.30	0.4 -
	10689.00	Towards DROP 50%	Towards LEFT 50%	2.27	-2	0.09	0.4 -	41.73	-7	-0.48	-0.2 -
	10783.00	Towards BUILD 40%	Towards LEFT 40%	1.62	-7	-1.06	-1.2 -	40.81	-10	-0.65	-0.2 -
	10876.00	Towards BUILD 80%	Towards LEFT 60%	-0.38	-21	-1.41	-0.4	40.18	-7	-0.12	0.6 -
	10970.00	Towards BUILD 100%	Towards LEFT 20%	-3.18	-30	-2.03	-0.7 -	38.83	-14	-1.53	-1.5 -
	11063.00	Towards DROP 70%	Towards LEFT 40%	-1.82	15	1.67	4.0 -	36.84	-21	-0.92	0.7 -
	11155.00	Towards DROP 20%	Towards LEFT 50%	-0.10	19	0.98	-0.8 -	35.86	-11	-0.30	0.7 -
	11247.00	NO CHANGE	Towards LEFT 40%	0.97	12	0.37	-0.7	35.10	-8	-0.65	-0.4 -
	11278.00	Towards DROP 20%	Towards LEFT 60%	1.14	6	0.28	-0.3 -	34.84	-8	-0.30	1.1 -
	11341.00	Towards DROP 10%	Towards LEFT 20%	1.49	5	-0,40	-1.1 -	34.13	-11	-1.00	-1.1 -
	11435.00	Towards DROP 50%	Towards LEFT 50%	1.35	-1	0.22	0.7 -	33.13	-11	-0.21	0.8 -
	11466.00	Towards DROP 20%	Towards LEFT 40%	1.44	3	0.13	-0.3 -	32.95	-6	-0.48	-0.9 -
	11528.00	Towards DROP 20%	Towards LEFT 40%	1.49	1	-0.05	-0.3 -	32.29	-11	-0.74	-0.4 -
_	11621.00	Towards BUILD 60%	Towards LEFT 40%	0.71	-8	-0.93	-0.9	31.30	-11	-0.48	0.3 -
	11715.00	Towards BUILD 80%	Towards LEFT 20%	-1.10	-19	-1.28	-0.4	29,58	-18	-1.62	-1.2
Record: Ⅰ 69 ▶ ▶ ▶ ▶ ★ of 69											

STONER ENGINEERING LLC

SES 3.0



- Steering Guidance
- O 3D Geosteering
- Cross-sections of TVD versus MD and 3DStratBlocks
- "Self-derived" Type Logs from the landing
- Geo model from grid data during well planning
- Revise the geologic model

- O 3D Graphics
- Multi-user environment
- Imports from LAS files
- US & Metric units
- Transfers data between SES users using XML
- THD & THD Logs



